

Modular Force10 Operating System (FTOS) software delivers inherent stability

24-port and 48-port GbE fixed configuration 1-RU switch with up to four 10 GbE ports

Scalable stacking technology supports 384 GbE ports with up to eight S50Vs

S-Series High Performance GbE/10 GbE Access Switch

The Force10 S25V and S50V bring core-like resiliency in a compact form factor to the network edge, enabling cost-effective scalability. These high performance and low latency Gigabit Ethernet switches deliver the critical functionality that advanced enterprise network edges demand.

Key Applications

Coupled with the E-Series and C-Series, which deliver unmatched resiliency and performance, the S25V and S50V enable IT managers to deploy a reliable end-to-end 10 GbE solution that spans from core to network edge.

- Line-rate GbE edge switches with 10 GbE uplinks for converged services and high bandwidth desktop applications
- Cost-effective PoE-enabled 10/100/1000Base-T wiring closet aggregation of VoIP phones, wireless access points, video cameras or other IEEE 802.3af-compliant devices

Key Features

The S25V and S50V are fixed configuration switches with PoE that deliver the reliability and scalability that wiring closets demand.

- 24 or 48 10/100/1000 ports in a 1-RU form factor
 - 20 or 44 ports 10/100/1000Base-T
 - 4 ports 10/100/1000Base-T shared with SFP ports
 - IEEE802.3af compliant PoE that provides up to 15.4 W per port and 790 W per switch
- Optional modules
 - 2-port 10 GbE LAN PHY (pluggable XFP modules)
 - 2-port 10 GbE (CX4)
 - 2-port 12 Gbps stacking
 - 1-port 24 Gbps stacking
- Modular FTOS with advanced monitoring and serviceability functions
- Suite of security, access control and wiring closet edge features for enterprise networks
- PowerSmart suite of intelligent power management features provide automatic sensing, provisioning and management of PoE power
- Full complement of standards-based Layer 2, IPv4 and IPv6 features for unicast and multicast applications
- Switching fabric capacity of up to 288 Gbps and forwarding capacity of more than 131 Mpps
- Stack up to eight S25N, S25P, S25V, S50N or S50V switches to deliver a scalable and flexible high capacity solution



Specifications: S-Series Power over Ethernet Switches

Ordering Information

ORDER NUMBER	DESCRIPTION
S25-01-GE-24V	24-port 10/100/1000Base-T chassis with PoE, 4 SFP ports, 2 modular slots, 1 AC + 1 DC power supply, FTOS software
S50-01-GE-48T-V-2	48-port 10/100/1000Base-T chassis with PoE, 4 SFP ports, 2 modular slots, 1 AC + 1 DC power supply, FTOS software
S50-01-10GE-2P	2-port 10 GbE XFP module
S50-01-10GE-2C	2-port 10 GbE CX4 module
S50-01-12G-2S	2-port 12 Gbps stacking module
S50-01-24G-1S	1-port 24 Gbps stacking module
S50-01-SSC-12G	60 cm stacking cable for S50-01-12G-2S
S50-01-LSC-12G	4 m stacking cable for S50-01-12G-2S
S50-01-SSC-24G	60 cm stacking cable for S50-01-24G-1S
S50-01-LSC-24G	4 m stacking cable for S50-01-24G-1S
S50-01-PSU-V	S25V/S50V redundant power supply unit
SW-SB-LATEST	Layer 3 FTOS software upgrade

Physical

S25V: 24 line-rate 10/100/1000Base-T ports

S50V: 48 line-rate 10/100/1000Base-T ports

4-ports SFP (shared)

1 RJ45 console/management port with RS232 signaling

Optional modules:

2 line-rate ports 10 Gigabit Ethernet XFP

2 line-rate ports 10 Gigabit Ethernet CX4

2 line-rate ports 12 Gigabit Stacking

1 line-rate port 24 Gigabit Stacking

Size: 1 RU, 1.7 h x 17.32 w x 16.73" d (4.3 h x 44 w x 42.5 cm d)

Weight: 15.62 lbs (7.10 kg)

ISO 7779 A-weighted sound pressure level:

S25V: 42.9 dBA at 73.4°F (23°C), S50V: 62.2 dBA at 73.4°F (23°C)

Power supply: 100–240 VAC 50/60 Hz, –48 VDC

Max. thermal output: S25V: 349 BTU/h, S50V: 497 BTU/h

Max. current draw per System:

6.5 A at 100/120 VAC, 3.25 A at 200/240 VAC, 11.5 A at –48 VDC

Max. power consumption:

S25V: 102 W, S50V: 146 W

Max. PoE power:

320 W using either AC or DC inputs

790 W using load sharing AC and DC inputs

Max. operating specifications:

Operating temperature: 32° to 122°F (0° to 50°C)

Operating humidity: 10 to 85% (RH), non-condensing

Max. non-operating specifications:

Storage temperature: –40° to 158°F (–40° to 70°C)

Storage humidity: 5 to 95% (RH), non-condensing

Reliability: S25V: MTBF 107,720 hours, S50V: MTBF 130,482 hours

Redundancy

Ring stacking topology with dynamic master election

Dual modular slots with up to four 10 GbE ports

Link aggregation across stack members

Power redundancy

Performance

MAC addresses: S25V: 16K, S50V: 32K

IPV4 routes: 4K

IPV6 routes: 2,500

Switching fabric capacity: S25V: 144 Gbps, S50V: 288 Gbps

User traffic capacity: S25V: 128 Gbps (95 Mpps)

S50V: 176 Gbps (131 Mpps)

Link aggregation: 8 links per group, 128 groups per stack

Stacking capacity: 96 Gbps per stack member

Queues per port: 4 queues

VLANs: 1024 VLANs with 4096 tag value support

Line-rate Layer 2 switching: all protocols, including IPv4 and IPv6

Line-rate Layer 3 routing: IPv4 and IPv6

LAG load balancing: based on Layer 2, IPv4 or IPv6 headers

Switching latency: <5 µs for 64 byte frames

IEEE Compliance

802.1AB LLDAP

802.1D Bridging, STP

802.1p L2 Prioritization

802.1Q VLAN Tagging, Double VLAN Tagging, GVRP

802.1s MSTP

802.1w RSTP

802.1X Network Access Control

802.3ab Gigabit Ethernet (1000BASE-T)

802.3ac Frame Extensions for VLAN Tagging

802.3ad Link Aggregation with LACP

802.3ae 10 Gigabit Ethernet (10GBASE-X)

802.3ak 10 Gigabit Ethernet (10GBASE-CX4)

802.3af Power over Ethernet

802.3i Ethernet (10BASE-T)

802.3u Fast Ethernet (100BASE-TX)

802.3x Flow Control

802.3z Gigabit Ethernet (1000BASE-X)

ANSI/TIA-1057 LLDP-MED

Force10 FRRP (Force10 Redundant Ring Protocol)

Force10 PVST+

MTU 9,252 bytes

RFC and I-D Compliance

General Internet Protocols

768	UDP	1321	MD5
793	TCP	1350	TFTP
854	Telnet	2474	Differentiated Services
959	FTP	3164	Syslog

General IPv4 Protocols

791	IPv4	1812	Routers
792	ICMP	1858	IP Fragment Filtering
826	ARP	2131	DHCP (server and relay)
1027	Proxy ARP	2338	VRRP
1035	DNS (client)	3021	31-bit Prefixes
1042	Ethernet Transmission	3046	DHCP Option 82
1191	Path MTU Discovery	3069	Private VLAN
1305	NTPv3	3128	Tiny Fragment Attack Protection
1519	CIDR		
1542	BOOTP (relay)		

General IPv6 Protocols

1981	Path MTU Discovery (partial)	2463	ICMPv6
		2464	Ethernet Transmission
2460	IPv6	2675	Jumbograms
2461	Neighbor Discovery (partial)	3587	Global Unicast Address Format
2462	Stateless Address Autoconfiguration (partial)	4291	Addressing

RIP

1058	RIPv1	2453	RIPv2
------	-------	------	-------

OSPF

2154	MD5	3623	Graceful Restart
1587	NSSA	4222	Prioritization and Congestion Avoidance
2328	OSPFv2		
2370	Opaque LSA		

BGP

1997	Communities	2918	Route Refresh
2385	MD5	3065	Confederations
2439	Route Flap Damping	4360	Extended Communities
2796	Route Reflection	4893	4-byte ASN
2842	Capabilities	5396	4-byte ASN Representation
2858	Multiprotocol Extensions		

draft-ietf-idr-bgp4-20 BGPv4

draft-ietf-idr-restart-06 Graceful Restart

Multicast

1112	IGMPv1		
2236	IGMPv2		
3376	IGMPv3		
3569	SSM for IPv4		
4541	IGMPv1/v2 Snooping		
draft-ietf-pim-sm-v2-new-05	PIM-SM		

Network Management

1155	SMlv1		
1156	Internet MIB		
1157	SNMPv1		
1212	Concise MIB Definitions		
1215	SNMP Traps		
1493	Bridges MIB		
1850	OSPFv2 MIB		
1901	Community-based SNMPv2		

2011 IP MIB

2012 TCP MIB

2013 UDP MIB

2024 DLSw MIB

2096 IP Forwarding Table MIB

2570 SNMPv3

2571 Management Frameworks

2572 Message Processing and Dispatching

2574 SNMPv3 USM

2575 SNMPv3 VACM

2576 Coexistence Between SNMPv1/v2/v3

2578 SMlv2

2579 Textual Conventions for SMlv2

2580 Conformance Statements for SMlv2

2618 RADIUS Authentication MIB

2665 Ethernet-like Interfaces MIB

2674 Extended Bridge MIB

2787 VRRP MIB

2819 RMON MIB (groups 1, 2, 3, 9)

2863 Interfaces MIB

2865 RADIUS

3273 RMON High Capacity MIB

3416 SNMPv2

3418 SNMP MIB

3434 RMON High Capacity Alarm MIB

3580 802.1X with RADIUS

5060 PIM MIB

ANSI/TIA-1057 LLDP-MED MIB

draft-grant-tacacs-02 TACACS+

draft-ietf-idr-bgp4-mib-06 BGP MIBv1

IEEE 802.1AB LLDP MIB

IEEE 802.1AB LLDP DOT1 MIB

IEEE 802.1AB LLDP DOT3 MIB

ruzin-mstp-mib-02 MSTP MIB (traps)

sFlow.org sFlowv5

sFlow.org sFlowv5 MIB (version 1.3)

FORCE10-BGP4-V2-MIB Force10 BGP MIB (draft-ietf-idr-bgp4-mibv2-05)

FORCE10-IF-EXTENSION-MIB

FORCE10-LINKAGG-MIB

FORCE10-COPY-CONFIG-MIB

FORCE10-MON-MIB

FORCE10-PRODUCTS-MIB

FORCE10-SS-CHASSIS-MIB

FORCE10-SMI

FORCE10-SYSTEM-COMPONENT-MIB

FORCE10-TC-MIB

FORCE10-TRAP-ALARM-MIB

Regulatory Compliance

Safety

UL/CSA 60950-1, 1st Edition

EN 60950-1, 1st Edition

IEC 60950-1, 1st Edition Including all National Deviations and Group Differences

EN 60825-1 Safety of Laser Products Part 1: Equipment Classification Requirements and User's Guide

EN 60825-2 Safety of Laser Products Part 2: Safety of Optical Fibre Communication Systems

FDA Regulation 21 CFR 1040.10 and 1040.11

Emissions

Australia/New Zealand: AS/NZS CISPR 22: 2006, Class A

Canada: ICES-003, Issue-4, Class A

Europe: EN 55022: 2006 (CISPR 22: 2006), Class A

Japan: VCCI V3/2007.04 Class A

USA: FCC CFR 47 Part 15, Subpart B, Class A

Immunity

EN 300 386 V1.3.3: 2005 EMC for Network Equipment

EN 55024: 1998 + A1: 2001 + A2: 2003

EN 61000-3-2: Harmonic Current Emissions

EN 61000-3-3: Voltage Fluctuations and Flicker

EN 61000-4-2: ESD

EN 61000-4-3: Radiated Immunity

EN 61000-4-4: EFT

EN 61000-4-5: Surge

EN 61000-4-6: Low Frequency Conducted Immunity

RoHS

All S-Series components are EU RoHS compliant.

The features and specifications are for FTOS. For SFTOS features and specifications, please refer to the SFTOS data sheet.

Force10 Networks, Inc.

350 Holger Way

San Jose, CA 95134 USA

www.force10networks.com

408-571-3500 PHONE

408-571-3550 FACSIMILE

© 2009 Force10 Networks, Inc. All rights reserved. Force10 Networks, Adit, E-Series, Traverse, and TraverseEdge are registered trademarks and Axius, C-Series, ExaScale, FTOS, MASTERseries, P-Series, S-Series, TeraScale, and TransAccess are trademarks of Force10 Networks, Inc. All other company names are trademarks of their respective holders. Information in this document is subject to change without notice. Certain features may not yet be generally available. Force10 Networks, Inc. assumes no responsibility for any errors that may appear in this document.

SSDS03

609 v4.2

